

MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS
757 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

PRODUCT DATA SHEET
26W10 CLEAR EMULSION

DESCRIPTION: CLEAR EMULSION is a clear, water based poly vinyl solution with a low semi gloss sheen. It is normally used as glazing medium, glitter adhesive, sealer for sheen adjustments.

RECOMMENED USE: Use as a water based glaze medium, bronzing liquid for metallic powders, glitter adhesive and sealer. When used as a sealer, handle with care as the film may show finger prints under certain conditions. Also may be added to interior flat vinyl-acrylic paints to raise the sheen slightly, or to glossy vinyl-acrylic enamel to lower the sheen slightly.

Note: such additions of clear emulsions could reduce hiding performance of the paint.

SURFACE PREPARATION: Standard procedures and practices which are normally followed in the painting profession should be used to clean and prepare the surfaces before painting begins. All surfaces must be clean, dry, and free of dust, dirt, grease, rust, loose paint, or other foreign substances. Remove all loose, flaking, or chalking surfaces.

TINTING: **Glazes:** add universal water based colorants or VARA-BOND FLAT STUDIO COLORS or Acry-Luster semi-gloss Studio Colors to achieve the desired tone. **Bronzing Medium:** add Bronzing powders at a rate of about 1 to 2 pounds per gallon to achieve proper color and coverage. Colorants may also be added to adjust the metallic powders. Note: Aluminum powders could cause gassing in an enclosed container. Use caution when storing (do not seal lid tightly). **Glitter:** glitter may be added to the surface immediately after coating with clear emulsion, or small, fine glitter may be mixed into the liquid before brushing or rolling (do not attempt to spray). If glitter is mixed into a liquid, it must be stirred regularly to prevent setting.

APPLICATION: It may be applied with brush, roller or spray. Apply this paint when temperature is above 50 degrees Fahrenheit. Provide fresh air ventilation during and after application.

DENSITY: 11.16 lb per gallon on white color, varies depending on colors

NON-VOLATILE(Wt %): 48.9 for white color

NON-VOLATILE(Vol%): 32.9 for white color

VISCOSITY: 85 – 100 KU

DRYING TIME: Dry to touch – 1 to 2 hours, to recoat – 2 to 4 hours.

Drying time also depends on surface temperature and relative humidity.

THINNING: Thin with water if needed.

COVERAGE: 300-400 sq. ft. per gallon. Actual coverage may vary depending surface conditions and application technique.

CLEAN UP: Warm, soapy water.

V.O.C.: Less than 50 grams per liter.

CAUTION : Do not take internally. Avoid contact with eyes, prolonged contact with skin or breathing of spray mists. Use with adequate ventilation. Clean hand and contaminated skins after use.

MANN BROTHERS PREMIUM PAINTS & FINISHING PRODUCTS

757 N. La Brea Blvd., Hollywood, CA 90038 TEL: 323.936-5168

WARNING: Do not apply if surface, container or air temperature is below **50 degree F.**

NOTICE: Purchaser is responsible for legal disposal of containers. Close container after each use.
Do not take internally. **Keep out of reach of children. Keep from freezing.**

CONTAINS: GLYCOL ETHER EB, MAY BE HARMFUL IF ABSORBED THROUGH SKIN.

FOR ADDITIONAL INFORMATION, SEE MATERIAL SAFETY DATA SHEET(MSDS) FOR THIS PRODUCT.